

OCTANE-R 15.0:1

1500W x 1 max power
2Ω

High Efficiency Class "D" Monoblock Amplifier
18dB LP Variable Crossover
18dB Variable Subsonic Filter
Low Pass Level (LPL) Port
Dimensions: 16.5L x 10.875W x 2.25H



OCTANE-R 8.0:1

800W x 1 max power
2Ω

High Efficiency Class "D" Monoblock Amplifier
18dB LP Variable Crossover
18dB Variable Subsonic Filter
Low Pass Level (LPL) Port
Dimensions: 14.75L x 10.875W x 2.25H



OCTANE-R 5.0:1

500W x 1 max power
2Ω

High Efficiency Class "D" Monoblock Amplifier
18dB LP Variable Crossover
18dB Variable Subsonic Filter
Low Pass Level (LPL) Port
Dimensions: 12.675L x 10.875W x 2.25H



OCTANE-R 2.0:1

200W x 1 max power
2Ω

High Efficiency Class "D" Monoblock Amplifier
18dB LP Variable Crossover
18dB Variable Subsonic Filter
Low Pass Level (LPL) Port
Dimensions: 11.75L x 10.875W x 2.25H



TUNER INSPIRED STYLING KITS

Optional Blue Anodized Top-plate and Neon Rails
Replaces Standard Aluminum Top-plate and Rails
Available in All Octane-R Series Amplifier Sizes



OCTANE-R 4.0:2

125W x 2 400W x 1 max power
4Ω stereo 4Ω bridged

2 Channel Power Amplifier
12dB HP/LP Variable Crossover
Full Range Auxiliary Output
Dimensions: 11.75L x 10.875W x 2.25H



OCTANE-R 2.5:2

80W x 2 250W x 1 max power
4Ω stereo 4Ω bridged

2 Channel Power Amplifier
12dB HP/LP Variable Crossover
Full Range Auxiliary Output
Dimensions: 8.75L x 10.875W x 2.25H



OCTANE-R 8.0:4

125W x 4 400W x 2 max power
4Ω stereo 4Ω bridged

4 Channel Power Amplifier
12dB HP/LP Variable Crossover
Full Range Auxiliary Output
Dimensions: 15.75L x 10.875W x 2.25H



OCTANE-R 5.0:4

80W x 4 250W x 2 max power
4Ω stereo 4Ω bridged

4 Channel Power Amplifier
12dB HP/LP Variable Crossover
Full Range Auxiliary Output
Dimensions: 13.75L x 10.875W x 2.25H



OCTANE-R 9.0:5

125W x 4 400W x 1 max power
4Ω stereo - front/rear 2Ω - subwoofer

5 Channel Power Amplifier
12dB HP/LP Variable Crossover
Separate Front/Rear/Sub Inputs
Low Pass Level (LPL) Port
Dimensions: 19.75L x 10.875W x 2.25H



The Octane-R 5.1 MT brings unprecedented flexibility, six discrete channels of amplifier power, Dolby Digital Decoding and an on screen interface - all in one compact package.

OCTANE-R 5.1 MT

100W x 5 + 200W x 1 max power
4Ω stereo 4Ω mono

6 Channel Power Amplifier
12dB HP Variable Crossover
24dB LP Variable Crossover
24 Bit AD/DA Processing
Dolby Digital 5.1 / Pro-Logic Decoding
Phantom 4.1 Processing
6 Independent Channel Level Controls
Full GUI Menu for On-Screen Control
Test Tone Levels for all Channels
Optical (Toslink) Input
Coaxial Input
2 Selectable Analog Input
IR Eye for Remote Control (Included)
Remote Turn-On Output for Other Devices
Dimensions: 10L x 6W x 2H



The Octane-ZR Subwoofers and Component Sets are designed and engineered to excel under high power applications.

OCTANE-ZR 12D4/12D2

350/700W
RMS/Peak

12d4: 12 inch, 8/2 ohm Subwoofer
12d2: 12 inch, 4/1 ohm Subwoofer
Integrated Rubber Mounting Gasket
2.0 inch High Temperature Voice Coil
30mm Peak to Peak Excursion
Cast Aluminum Basket
Sensitivity: 90dB (1W/1M)



OCTANE-ZR 10D4/10D2

200/400W
RMS/Peak

10d4: 10 inch, 8/2 ohm Subwoofer
10d2: 10 inch, 4/1 ohm Subwoofer
Integrated Rubber Mounting Gasket
2.0 inch High Temperature Voice Coil
30mm Peak to Peak Excursion
Cast Aluminum Basket



The all-new Octane-R Series Amplifiers are big-power amplifiers with street racing cosmetics. Overbuilt and indestructible power supplies provide rock solid stability and reliability.

The all-new Octane-R and Octane-ZR Series speakers incorporate many of the same tuner-inspired cosmetic attributes as the amplifiers, such as aluminum plated cone, injection molded dustcap that matches the amplifier badge and an illuminated logo that glows blue when the system is powered on.

OCTANE-R 12/12D

250/500W
RMS/Peak

12: 12 inch, 4 ohm Subwoofer
12d: 12 inch, 8/2 ohm Subwoofer
1.5 inch High Temperature Voice Coil
28mm Peak to Peak Excursion
Stamped Steel Basket
Sensitivity: 91dB (1W/1M)



OCTANE-R 10/10D

200/400W
RMS/Peak

10: 10 inch, 4 ohm Subwoofer
10d: 10 inch, 8/2 ohm Subwoofer
1.5 inch High Temperature Voice Coil
28mm Peak to Peak Excursion
Stamped Steel Basket
Sensitivity: 90dB (1W/1M)



OCTANE-R 69.0 COAX

70/140W
RMS/Peak

6 x 9 inch Coaxial
Frequency Response: 75Hz - 20kHz
Sensitivity: 91dB (1W/1M)



OCTANE-R 57.0 COAX

70/140W
RMS/Peak

5 x 7 inch Coaxial
Frequency Response: 85Hz - 20kHz
Sensitivity: 90dB (1W/1M)
Dimensions: 14.5L x 10.875W x 2.25H



OCTANE-R 46.0 COAX

45/90W
RMS/Peak

4 x 6 inch Coaxial
Frequency Response: 90Hz - 20kHz
Sensitivity: 89dB (1W/1M)
Dimensions: 14.5L x 10.875W x 2.25H



OCTANE-ZR 6.5 COMP

75/150W
RMS/Peak

6.5 inch (165mm)
2-Way Component System
25mm Silk Dome Tweeter
External 24dB Passive Crossover
Frequency Response: 65Hz - 20kHz
Sensitivity: 90dB (1W/1M)



OCTANE-ZR 6.0 COMP

75/150W
RMS/Peak

6.0 inch (150mm)
2-Way Component System
25mm Silk Dome Tweeter
External 24dB Passive Crossover
Frequency Response: 65Hz - 20kHz
Sensitivity: 90dB (1W/1M)



OCTANE-ZR 5.0 COMP

75/150W
RMS/Peak

5.25 inch (130mm)
2-Way Component System
25mm Silk Dome Tweeter
External 24dB Passive Crossover
Frequency Response: 75Hz - 20kHz



OCTANE-R 6.5 COMP

70/140W
RMS/Peak

6.5 inch (165mm)
2-Way Component System
2mm Mylar Tweeter
Frequency Response: 60Hz - 24kHz
Sensitivity: 90dB (1W/1M)



OCTANE-R 6.0 COMP

70/140W
RMS/Peak

6.0 inch (150mm)
2-Way Component System
2mm Mylar Tweeter
Frequency Response: 60Hz - 24kHz
Sensitivity: 90dB (1W/1M)



OCTANE-R 5.0 COMP

70/140W
RMS/Peak

5.25 inch (130mm)
2-Way Component System
2mm Mylar Tweeter
Frequency Response: 85Hz - 24kHz
Sensitivity: 89dB (1W/1M)



OCTANE-R 6.5 COAX

60/120W
RMS/Peak

6.5 inch (165mm) Coaxial
Frequency Response: 80Hz - 20kHz
Sensitivity: 90dB (1W/1M)



OCTANE-R 6.0 COAX

60/120W
RMS/Peak

6.0 inch (150mm) Coaxial
Frequency Response: 80Hz - 20kHz
Sensitivity: 90dB (1W/1M)



OCTANE-R 5.0 COAX

50/100W
RMS/Peak

5.25 inch (130mm) Coaxial
Frequency Response: 90Hz - 20kHz
Sensitivity: 89dB (1W/1M)



OCTANE-R 4.0 COAX

45/90W
RMS/Peak

4.0 inch (100mm) Coaxial
Frequency Response: 100Hz - 20kHz
Sensitivity: 88dB (1W/1M)



OCTANE-R 3.0 COAX

40/80W
RMS/Peak

3.5 inch (90mm) Coaxial
Frequency Response: 120Hz - 20kHz
Sensitivity: 88dB (1W/1M)

